# **SKID STEER-MAINTENANCE REPORT**

DATE OF INSPECTION	
UNIT #	
HOUR METER	
INSPECTION COMPLETED BY	

#### **SERVICE INTERVAL: EVERY 10 HOURS OR DAILY**

Maintenance Requirement	Check	Grease	Change	Clean	AM	PM
Engine oil level						
Hydraulic oil level						
Anti-freeze						
Torque Final Drive Bolts - 200 ft/lb						
Boom Pivots						
Bucket Pivots & Attachment Pins						
Tilt Test						
Horn/Lights & Windshield Wiper						
Back up alarm						
Gauges Functioning						
Check for leaks & cracks						
Spill Kit/First Aid Kit/Fire Extinguisher						
Clean out engine bay from debris						
Clean out air filter & Cover/Nipple						
Clean rad from debris						
Axle Bearings - Lubricate (takes lots)						
Quick coupler - clean/inspect						
Seat Belt - inspect						
Brushing-remove cover check motor bolts & blade						
Track - inspect/adjust						
Track Roller and idler - inspect/replace						
Clean engine compartment-remove combustibles						

#### **SERVICE INTERVAL: EVERY 40 HOURS**

Maintenance Requirement	Check	Grease	Change	Clean	Total Hours
Mulcher Head cover plates removed-clean-inspect					
Remove side plate inspect belt tension					
Lift cab clean out combustibles from around pumps					
Remove plate & clean debris from around quick connect					
pins/levers					

## **SERVICE INTERVAL: EVERY 250 HOURS**

Maintenance Requirement	Check	Grease	Change	Clean	Total Hours
Final Drive oil (check)					
Belts - Remove plastic guard - inspect/adjust/replace					

## **SERVICE INTERVAL: EVERY 500 HOURS**

Maintenance Requirement	Check	Grease	Change	Clean	Total Hours
Final Drive oil - change					
Fuel filter - change					
Engine oil - change					
Hydraulic system oil sample filter - replace					

## SERVICE INTERVAL: EVERY 2000 HOURS - HYDRAULIC OIL CHANGE

Maintenance Requirement	Check	Grease	Change	Clean	Total Hours
Fuel up unit					
Clean out behind Skid Plates <b>x2</b> & under cab/air box					
-under lift arms by cylinders					
(lift cab off) $\rightarrow$ re-assemble Skid Plates & Cab Bolts					
Clean & lube Attachment Pins					
Power wash Rad good					
Check Tracks - 1" - 1.5" of play on bottom of track					
lift front with bucket					
Vacuum cab & clean windows					
Check battery terminals - Tight & not corroded					
Clean out					
Inspect/clean cab filter					
Inspect rubber door seal					
Inspect Attachment & both plates					

NOTES:

NUTES:		